

Smart DC Hipot Model 460-6E



Testing Applications

Measures output voltage, leakage current, insulation resistance, and polarization index

- Output voltage up to 60 kV DC
- Leakage current up to 6 mA

The model 460-6E smart DC hipot is a cutting-edge dielectric test instrument designed with an emphasis on operator safety, versatility and ease of use. Complying with the most rigorous safety requirements, the system is divided into two modules, a control unit and a high voltage generation unit. Additional safety features include an emergency stop switch and a built-in sound alarm. Furthermore, the ability to fully remote control the instrument from an Android device — both to program the settings as well as to perform the tests — provides increased safety protection and greater comfort for the operator. A built-in microprocessor allows the user to adjust the output voltage, test duration, maximum leakage current and ramp slope, allowing for more complex tests to be carried out automatically.

- **Lightweight** and **ruggedly constructed** for years of field use
- **Remote control** via **Bluetooth** connection to **Android™** devices
- **Built-in** memory



Safety and Design Features

- Remote control via Bluetooth
- Digital & bar graph reading
- “Pass-Fail” LED indicator
- Audible alarm
- Emergency Off pushbutton
- Adjustable parameters: voltage, maximum leakage current, ramp and test duration
- Self-detection of sparks
- Built-in memory
- USB interface
- Software for data management
- IP54 protection (with lid closed)
- Complies with IEC 61010-1



Specifications

INPUT	Voltage/Current	120 or 240 V, 400 VA
	Frequency	50/60 Hz
DC OUTPUT	Voltage/Current	0-60 kV, 6 mA
	Ripple	<2%
	Polarity	Negative output, positive ground
TEST VOLTAGE	Resolution	100 V between 10 kV and 60 kV 10 V up to 9.99 kV
	Accuracy	±(2% of nominal value ±2 digits) with 1 mA load
LEAKAGE CURRENT MEASUREMENT		Max. 6 mA
	Resolution	0.1 mA
	Accuracy	±(2% of nominal value ±2 digits)
INSULATION RESISTANCE MEASUREMENT		From 500 kΩ to 32 GΩ
	Accuracy	±5% of the measured value
BUILT-IN TIMER		Up to 30 minutes
OPERATING TEMPERATURE		23°F to 122°F (-5°C to 50°C)
STORAGE TEMPERATURE		-13°F to 158°F (-25°C to 70°C)
HUMIDITY		<95%, non-condensing
DIMENSIONS & WEIGHT	Controls	17.5" L x 14.2" W x 7.5" H (450 x 360 x 190 mm) 15.43 lbs (7 kgs)
	High Voltage Module	17.5" L x 14.2" W x 7.5" H (450 x 360 x 190 mm) 15.65 lbs (7.1 kgs)
ACCESSORIES included		1 Interconnection cable (controller module), 9.84' (3 m)* 1 High voltage cable, 19.68' (6 m)* 1 Return cable HV, 19.68' (6 m)* 1 Protective grounding cable, 16.40' (5 m) 1 Power cable 1 USB cable 1 Carrying bag 1 User guide 1 Software *Different lengths available upon request.



PHENIX TECHNOLOGIES

WORLD HEADQUARTERS

Phenix Technologies, Inc.
75 Speicher Drive
Accident, MD 21520 USA
Ph: +1.301.746.8118
Fx: +1.301.895.5570
Info@phenixtech.com

BRANCH OFFICES

Phenix Systems AG
Riehenstrasse 62A, 4058 Basel, Switzerland
Ph: +41.61.383.2770, Info@phenixsystems.com

Phenix Asia
Zhong Cheng Rd, Sec 1, No 177, 2F, Taipei 11148 Taiwan
Ph: +886.2.2835.9738, Fx: +886.2.2835.9879, Info@phenixasia.com

ISO
9001:2008
Compliant

